

SAFETY DATA SHEET



Date Prepared : 06/18/2015

SDS No : 5803

Date Revised : 06/18/2015

Revision No : 1

JOHN-HENRY 2

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: JOHN-HENRY 2**GENERAL USE:** Alkaline Truck Wash (Part 2 of Two Step Wash System)**PRODUCT CODE:** 5803**MANUFACTURER**

JOHN-HENRY Enterprises, Inc.
 2813 Richland Ave
 Metairie, LA 70002
Emergency Contact: H. Zeller
Emergency Phone: 504-888-8989

24 HR. EMERGENCY TELEPHONE NUMBERS

US/Canada: 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Damage/Irritation (Reversible), Category 1A

Skin Corrosion/Irritation (reversible), Category 2

GHS LABEL

CORROSIVE: Causes severe irritation and can cause burns and permanent damage to eyes. Causes moderate to severe irritation and possibly burns to skin. Mists and spray can irritate eyes, nose, throat, and respiratory system. Ingestion can cause severe irritation, burns and tissue damage to mouth, throat, esophagus, and stomach. May be harmful or fatal if swallowed. Vapors can cause nervous system depression.



Irritant



CORROSIVE

SIGNAL WORD: DANGER**HAZARD STATEMENTS**

H335: May cause respiratory irritation.

H314: Causes severe skin burns and eye damage.

H290: May be corrosive to metals.

PRECAUTIONARY STATEMENTS**Prevention:**

P102: Keep out of reach of children.

P103: Read label before use.

P262: Do not get in eyes, on skin, or on clothing.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

75990X3S: Keep only in original container. Store in a well-ventilated place. Keep container tightly closed.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Causes severe irritation and burns to skin. Causes severe irritation, burns, and damage to eyes. Mists and vapors can cause irritation to eyes, nose, throat, and respiratory tract. Ingestion can damage mouth, throat, and other tissues and may be fatal. Vapors can cause nausea, dizziness, nausea, stupor, vomiting, headache, and/or irritation to nose, throat, and respiratory system.

POTENTIAL HEALTH EFFECTS

EYES: Corrosive, contact causes severe eye burns.

SKIN: Contact causes severe skin irritation and possible burns.

INGESTION: Causes severe irritation and possibly burns to mouth, throat, esophagus, and gastrointestinal system. May cause gastrointestinal discomfort, including nausea, vomiting, diarrhea, etc

INHALATION: Mists, sprays, or vapor can be irritating to eyes and respiratory tract.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Sodium Hydroxide	< 2	1310-73-2
Glycol ether	< 10	Proprietary
Other ingredients are not hazardous or are present at levels that do not present a significant hazard.		> 80
		mixture

4. FIRST AID MEASURES

EYES: Gently hold eyelids open and immediately flush eyes with water for at least 15 minutes or until pain eases. Remove contact lenses if possible. Seek medical attention, especially if there are visible burns or damage to or around eyes.

SKIN: Remove contaminated clothing and footwear. Wash with soap and water. Get medical attention if irritation or rash develops or persists or if symptoms of CNS depression develop or occur.

INGESTION: Get immediate emergency medical attention (Call 911). Rinse mouth with water. Do not induce vomiting unless instructed to do so by poison center or physician. Give water, milk, or dilute citrus juice unless unconscious or convulsing. Keep patient warm, quiet, and comfortable and treat for shock.

INHALATION: If affected by spray or mist, move to fresh air. Seek medical attention if symptoms persist or worsen.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe irritation or pain, tearing, redness, blurring and/or temporary or permanent loss of vision. May cause burns to and around eyes.

SKIN: Prolonged or repeated contact may produce irritation, redness, edema, burning or itching, rash, etc. Glycol ether can be absorbed by skin and product dizziness, nausea, vomiting, and other signs of CNS depression

INGESTION: Causes irritation to mouth, throat, esophagus, and GI tract. Can cause gastrointestinal discomfort, including nausea, vomiting, and diarrhea.

INHALATION: Vapors, spray or mists can irritate eyes, nose, throat, and respiratory tract. Vapors can cause dizziness, drowsiness, nausea, headache, drunkenness, vomiting, unconsciousness, and other anesthetic effects.

NOTES TO PHYSICIAN: Treat symptomatically. If burns are present, treat for thermal burns.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Applicable - Water based product with no flashpoint.

EXTINGUISHING MEDIA: Not applicable - water based product. After water has evaporated, use water (fog or spray) or chemical foam on burning solids.

HAZARDOUS COMBUSTION PRODUCTS: After water has evaporated, burning solids will produce oxides of carbon, nitrogen, and sulfur, organosulfur, organonitrogen, and hydrocarbon residues and acrid fumes

EXPLOSION HAZARDS: Containers can burst if exposed to flames or high temperatures.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting chemical fires. Use water fog or spray to cool containers.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and absorb spilled material. Dispose of contaminated absorbant properly. Wash spill area with water.

LARGE SPILL: Wear appropriate PPE. Remove uninvolved personnel from area. Stop flow. Contain spill and keep from entering sewer or surface waterways. Collect spill into suitable, properly labeled containers for use or disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes and prolonged contact with skin. Read and understand product label and SDS before handling any chemical. Always wear recommended personal protective equipment. Follow label cautions and instructions.

STORAGE: Store in original containers in well ventilated area. Keep containers closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Sodium Hydroxide	TWA		2		
Glycol ether	TWA	50	240	20	97

ENGINEERING CONTROLS: Maintain sufficient ventilation in storage and use areas to prevent the accumulation of product vapors, spray, or mists. Provide local exhaust for enclosed areas.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Avoid eye contact. Wear safety glasses or goggles

SKIN: Avoid prolonged or repeated contact. Wear rubber, latex, or other chemical resistant gloves.

RESPIRATORY: Use with adequate ventilation. Wear a NIOSH approved acid absorbing, air purifying respirator where mists or spray are excessive or exceed exposure limits.

WORK HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or using the facilities after handling any chemical product.

OTHER USE PRECAUTIONS: Working eyewash stations and safety showers should be located in or near all areas where chemicals are stored or used.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: mild, ether-like

APPEARANCE: clear, red liquid

pH: > 12.5

Notes: as made

PERCENT VOLATILE: 82 - 88% (w/w)

FLASH POINT AND METHOD: > (200°F)

VAPOR PRESSURE: Same as water (approximately)

VAPOR DENSITY: Same as water (approximately)

BOILING POINT: greater than 212 deg F

FREEZING POINT: less than 32 deg F (0 deg C)

SOLUBILITY IN WATER: Complete in all proportions.

EVAPORATION RATE: Same as water (approximately)

SPECIFIC GRAVITY: 1.01 to 1.03

VISCOSITY: Same as water (approximately)

(VOC): ~ 9.500 percent (v/v)

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: No

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, and nitrogen, organonitrogen, and and hydrocarbon residues

INCOMPATIBLE MATERIALS: Concentrated acids, oxidizing agents, metals such as aluminum or zinc, amines, ammonia, organic materials, reducing agents

11. TOXICOLOGICAL INFORMATION

ACUTE

NOTES: No toxicity data available for product

EYE EFFECTS: Severe irritation, pain, burns, temporary or permanent loss of vision.

SKIN EFFECTS: Prolonged or repeated exposure can cause moderate to severe irritation. dermatitis, rash, sensitization. Prolonged one time exposure may cause burns.

CARCINOGENICITY

Chemical Name	General Toxicity
Glycol ether	Confirmed animal carcinogen with unknown relevance to humans - Group A3

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Unused or undiluted product constitutes a hazardous waste. Follow all appropriate local, state, and Federal disposal regulations. Surfactants and other organic components are biodegradable. Collect and neutralize spent solutions and discharge to a waste water treatment facility.

FOR LARGE SPILLS: See Section 6

EMPTY CONTAINER: Triple rinse container thoroughly with water and recycle.

RCRA/EPA WASTE INFORMATION: Unused or undiluted product would constitute an RCRA regulated hazardous waste due to corrosivity (CORROSIVE WASTE - D002, pH equal to or greater than 12.5)

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: NA1760, Compound, Cleaning liquid (contains sodium hydroxide), 8, II

VESSEL (IMO/IMDG)

SHIPPING NAME: UN1760, CORROSIVE LIQUID, N.O.S. (SODIUM HYDROXIDE SOLUTION), 8, III

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION



Corrosive

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute health hazard (eye and skin irritation/corrosion)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Sodium Hydroxide	< 2	1,000

CERCLA RQ: greater than 10000 lbs (as supplied)

EPA

EPA RQ INGREDIENT: Sodium Hydroxide

EPA RQ PRODUCT: greater than 10000 lbs (as supplied)

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Sodium Hydroxide	1310-73-2
Glycol ether	Proprietary

TSCA STATUS: All ingredients are included on the TSCA Inventory or are exempt

CALIFORNIA PROPOSITION 65: Contains no substances known to the State of California to cause cancer, birth defects, or reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE: Convert to GHS format

APPROVED BY: H. Zeller


PREPARED BY: CSCC **Date Revised:** 06/18/2015

REVISION SUMMARY: This SDS replaces the 06/18/2015 SDS.

HMIS RATING

HEALTH	<input type="checkbox"/>	3
FLAMMABILITY	<input type="checkbox"/>	0
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	X

NFPA CODES



GENERAL STATEMENTS: Amounts specified herein (other than for regulatory purposes) are typical and do not represent a specification. Unspecified or unlisted components are proprietary, do not present a hazard at levels present, are not hazardous, and/or are present at levels below reportable limits. Exact percentage values for all components are proprietary in accordance with 29 CFR 1910.1200(i).

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for its accuracy and/or completeness. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health or physical hazards and should be used with caution. Certain hazards are described herein, but no guarantee is made that these are the only hazards associated with the material that exist.