

SAFETY DATA SHEET



Date Prepared : 07/04/2015

SDS No : 5436

B-5925

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: B-5925
GENERAL USE: Boiler Treatment
PRODUCT CODE: 5436

MANUFACTURER

JOHN-HENRY Enterprises, Inc.
 2813 Richland Ave
 Metairie, LA 70002
Emergency Contact: H. Zeller
Emergency Phone: 504-888-8989

24 HR. EMERGENCY TELEPHONE NUMBERS

US/Canada: 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Damage/Irritation (Reversible), Category 2
 Skin Corrosion/Irritation (reversible), Category 2

GHS LABEL

Causes severe irritation and possibly burns to eyes. Causes moderate to severe irritation and possibly burns to skin. Mists and spray can irritate eyes, nose, throat, and respiratory system.



CORROSIVE

SIGNAL WORD: WARNING**HAZARD STATEMENTS**

H319: Causes serious eye irritation.
 H315: Causes skin irritation.
 H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS**Prevention:**

P102: Keep out of reach of children.
 P103: Read label before use.
 P262: Do not get in eyes, on skin, or on clothing.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 75990X3S: Keep only in original container. Store in a well-ventilated place. Keep container tightly closed.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Causes severe irritation to skin. Causes severe irritation and damage to eyes. Mists and vapors can cause irritation to eyes, nose, and throat. Ingestion can damage mouth, throat, and other tissues and may be fatal.

POTENTIAL HEALTH EFFECTS

EYES: Severely irritating and may cause temporary blurring of vision.

SKIN: Prolonged contact can cause severe skin irritation and possible burns.

INGESTION: Causes irritation and burns to mouth, throat, esophagus, and gastrointestinal system. May cause gastrointestinal discomfort, including nausea, vomiting, diarrhea, etc, and may be fatal.

INHALATION: Mists or sprays can be moderately to severely irritating to eyes and respiratory tract.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Alkaline Builder	< 5	Proprietary
Organic amine	< 5	Proprietary
Other ingredients are not hazardous or are present at levels that do not present a significant hazard.	> 88	mixture

4. FIRST AID MEASURES

EYES: Gently hold eyelids open and immediately flush eyes with water for at least 15 minutes or until pain eases. Remove contact lenses if possible. Seek medical attention, especially if there are visible burns or damage to or around eyes.

SKIN: Remove contaminated clothing and footwear. Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Get immediate emergency medical attention (Call 911). Rinse mouth with water. Do not induce vomiting unless instructed to do so by poison center or physician. Give water, milk, or dilute citrus juice unless unconscious or convulsing. Keep patient warm, quiet, and comfortable and treat for shock.

INHALATION: If affected by vapors, spray or mist, move to fresh air. Seek medical attention if symptoms persist or worsen. If breathing is difficult, give oxygen and get immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe irritation or pain, tearing, redness, blurring and/or temporary loss of vision

SKIN: Prolonged exposure can cause moderate to severe irritation and possibly burns.

INGESTION: Causes moderate to severe irritation to mouth, throat, esophagus, and GI tract. Can cause gastrointestinal discomfort, including nausea, vomiting, and diarrhea.

INHALATION: Spray or mists can irritate eyes, nose, throat, and respiratory tract.

NOTES TO PHYSICIAN: Treat symptomatically. If burns are present, treat for thermal burns.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Applicable - Water based product with no flashpoint.

EXTINGUISHING MEDIA: Not applicable - water based product. After water has evaporated, use water (fog or spray) or chemical foam on burning solids.

HAZARDOUS COMBUSTION PRODUCTS: After water has evaporated, burning solids will produce oxides of carbon, nitrogen and phosphorus, organonitrogen, organophosphorus, and hydrocarbon residues and acrid fumes

EXPLOSION HAZARDS: Containers can burst if exposed to flames or high temperatures.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting chemical fires. Use water fog or spray to cool containers.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear recommended PPE. Contain and absorb spilled material. Dispose of contaminated absorbant properly. Wash spill area with water.

LARGE SPILL: Wear appropriate PPE. Remove uninvolved personnel from area. Stop flow. Contain spill and keep from entering sewer or surface waterways. Collect spill into suitable, properly labeled containers for use or disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes and prolonged contact with skin. Read and understand product label and SDS before handling any chemical. Always wear recommended personal protective equipment. Follow label cautions and instructions.

STORAGE: Store in original containers in well ventilated area. Keep containers closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Maintain sufficient ventilation in storage and use areas to prevent the accumulation of product vapors, spray, or mists. Provide local exhaust for enclosed areas.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses or goggles and face shield when handling.

SKIN: Wear rubber, latex, or other chemical resistant gauntlet gloves and boots

RESPIRATORY: Use with adequate ventilation. Wear a NIOSH approved air purifying respirator where vapors, mists or spray are excessive or exceed exposure limits.

WORK HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or using the facilities after handling any chemical product.

OTHER USE PRECAUTIONS: Working eyewash stations and safety showers should be located in or near all areas where chemicals are stored or used.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: amine

APPEARANCE: clear, pale amber liquid

pH: 12.5 to 13.5

Notes: (5% in water)

PERCENT VOLATILE: Not determined

FLASH POINT AND METHOD: > (200°F) TCC

VAPOR PRESSURE: Same as water (approximately)

VAPOR DENSITY: Same as water (approximately)

BOILING POINT: greater than 212 deg F

FREEZING POINT: less than 32 deg F (0 deg C)

SOLUBILITY IN WATER: Complete in all proportions.

EVAPORATION RATE: Same as water (approximately)

SPECIFIC GRAVITY: 1.005 to 1.015

VISCOSITY: Same as water (approximately)

(VOC): ~ 4.000 percent (w/w)

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: No

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, nitrogen, and phosphorus, organophosphorus, organonitrogen, and hydrocarbon residues

INCOMPATIBLE MATERIALS: Concentrated acids, oxidizing agents, metals such as aluminum or zinc, ammonia and amines

11. TOXICOLOGICAL INFORMATION

ACUTE

NOTES: No toxicity data available for product

EYE EFFECTS: Severe irritation, pains, burns, temporary loss of vision.

SKIN EFFECTS: Prolonged or repeated exposure can cause moderate to severe irritation. dermatitis, rash, sensitization. Prolonged one time exposure may cause burns.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Unused or undiluted product constitutes a hazardous waste. Follow all appropriate local, state, and Federal disposal regulations. Surfactants and other organic components are biodegradable. Collect and neutralize spent solutions and discharge to a waste water treatment facility.

FOR LARGE SPILLS: See Section 6

EMPTY CONTAINER: Triple rinse container thoroughly with water and recycle.

RCRA/EPA WASTE INFORMATION: Unused or undiluted product would constitute an RCRA regulated hazardous waste due to corrosivity (CORROSIVE WASTE - D002, pH equal to or greater than 12.5)

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** UN1760, Corrosive Liquid, N.O.S. (contains diethylaminoethanol), 8, III**VESSEL (IMO/IMDG)****SHIPPING NAME:** UN3266, CORROSIVE, LIQUID, BASIC, INORGANIC, N.O.S. (contains diethylaminoethanol), 8, PG III**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**


Corrosive

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**311/312 HAZARD CATEGORIES:** Acute health hazard (eye and skin irritation/corrosion)**FIRE:** No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** No**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Alkaline Builder	Proprietary
Organic amine	Proprietary

CALIFORNIA PROPOSITION 65: Contains no substances known to the State of California to cause cancer.**16. OTHER INFORMATION****REASON FOR ISSUE:** Convert to GHS format**APPROVED BY:** H. Zeller**PREPARED BY:** CSCC **Date Prepared:** 07/04/2015**HMIS RATING**

HEALTH	<input type="checkbox"/>	3
FLAMMABILITY		0
PHYSICAL HAZARD		0
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	X

NFPA CODES**GENERAL STATEMENTS:** Amounts specified herein (other than for regulatory purposes) are typical and do not represent a specification.

Unspecified or unlisted components are proprietary, do not present a hazard at levels present, are not hazardous, and/or are present at levels below reportable limits. Exact percentage values for all components are proprietary in accordance with 29 CFR 1910.1200(i)

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for its accuracy and/or completeness. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health or physical hazards and should be used with caution. Certain hazards are described herein, but no guarantee is made that these are the only hazards associated with the material that exist.