

SAFETY DATA SHEET



Date Prepared : 5/26/2015
SDS No : Gladiator ES

GLADIATOR ES

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: GLADIATOR ES
GENERAL USE: Cement Truck Cleaner
PRODUCT CODE: 5458

MANUFACTURER

JOHN-HENRY Enterprises, Inc.
2813 Richland Ave
Metairie, LA 70002
Emergency Contact: H. Zeller
Emergency Phone: 504-888-8989

24 HR. EMERGENCY TELEPHONE NUMBERS

US/Canada: 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Damage, Category 1B
Skin Corrosion/Irritation, Category 1B

GHS LABEL

CORROSIVE. Causes severe irritation and burns to skin. Causes severe burns and damage to eyes. Mists and spray can be irritating to eyes, nose, throat, and respiratory tract. Harmful or fatal if swallowed.



CORROSIVE

SIGNAL WORD: DANGER**HAZARD STATEMENTS**

H314: Causes severe skin burns and eye damage.

PRECAUTIONARY STATEMENTS**Prevention:**

P102: Keep out of reach of children.
P103: Read label before use.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash ... thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
75990X3S: Keep only in original container. Store in a well-ventilated place. Keep container tightly closed.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Causes severe irritation and reversible burns to skin. Causes severe irritation and damage to eyes. Mists and vapors can cause irritation to eyes, nose, and throat. Ingestion can cause moderate to severe irritation and burns to mouth, throat, and gastrointestinal tract. May be fatal if swallowed.

POTENTIAL HEALTH EFFECTS

EYES: Corrosive, contact causes severe eye burns.

SKIN: Contact causes severe skin irritation and possible burns.

INGESTION: Causes severe irritation, burns, and damage to mouth, throat, esophagus, and stomach. May be fatal if swallowed

INHALATION: Mists or sprays can be moderately to severely irritating to eyes and respiratory tract.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Buffered Acid Salt Solution	< 60	Proprietary
Other ingredients are not hazardous or are present at levels that do not present a significant hazard.	> 40	mixture

4. FIRST AID MEASURES

EYES: Treat eye contact and a medical emergency. Gently hold eyelids open and immediately flush eyes with water for at least 15 minutes or until pain eases. Remove contact lenses if possible. Cover eyes loosely with sterile dressing and SEEK IMMEDIATE MEDICAL ATTENTION.

SKIN: Remove contaminated clothing and footwear. Flush off with copious amounts of running water. Seek medical attention for burns or if irritation persists or worsens.

INGESTION: Get immediate medical attention (call 911). Do not induce vomiting unless instructed to do so by poison center or physician. Give patient water or milk unless unconscious or convulsing. Keep patient warm and comfortable. Treat for shock.

INHALATION: If affected by vapors, spray or mist, move to fresh air. Seek medical attention if symptoms persist or worsen. Give oxygen if breathing is difficult and seek prompt medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Severe irritation or pain, blurring and loss of vision, permanent damage.

SKIN: Causes moderate to severe irritation and possibly burns.

INGESTION: Harmful or fatal if swallowed. Can cause irritation, gastric upset, burns and damage (corrosion) to mouth, throat, esophagus and gastrointestinal tract.

INHALATION: Spray or mists can severely irritate eyes, nose, throat, and respiratory tract causing coughing, sneezing, difficulty breathing, etc.

NOTES TO PHYSICIAN: Treat symptomatically. If burns are present, treat for thermal burns.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Applicable. Flash point greater than 200 deg F.

EXTINGUISHING MEDIA: Not applicable - water based product. After water has evaporated, use water (fog or spray) or chemical foam on burning solids.

HAZARDOUS COMBUSTION PRODUCTS: After water has evaporated, burning solids will produce oxides of carbon, nitrogen and sulfur, organosulfur, organonitrogen and hydrocarbon residues and acid fumes

EXPLOSION HAZARDS: Containers can burst if exposed to flames or high temperatures.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting chemical fires. Use water fog or spray to cool containers and knock down acidic vapors.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear recommended PPE. Ventilate the area and remove uninvolved personnel. Contain and absorb spilled material. Dispose of contaminated absorbant properly. Wash spill area with water.

LARGE SPILL: Wear appropriate PPE. Ventilate the area and remove uninvolved personnel from area. Stop flow. Contain spill and keep from entering sewer or surface waterways. Collect spill into suitable, properly labeled containers for use or disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

HANDLING: Read and understand product label and SDS before handling any chemical. Always wear recommended personal protective equipment. Follow label instructions.

STORAGE: Store in original containers in well ventilated area away from strong alkalies or oxidizing materials. Keep containers tightly closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Maintain sufficient ventilation in storage and use areas to prevent the accumulation of product vapors, spray, or mists. Provide local exhaust for enclosed areas.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses or goggles and face shield when handling.

SKIN: Wear rubber, latex, or other chemical resistant gauntlet gloves and boots

RESPIRATORY: Use with adequate ventilation. Wear a NIOSH approved acid absorbing, air purifying respirator where mists or spray are excessive or exceed exposure limits.

PROTECTIVE CLOTHING: Wear chemically resistant rain suit if there is a possibility of exposure to spray or heavy mists

WORK HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or using the facilities after handling any chemical product.

OTHER USE PRECAUTIONS: Working eyewash stations and safety showers should be located in or near all areas where chemicals are stored or used.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Characteristic

APPEARANCE: clear, green liquid

pH: < 2.0

Notes: as made

PERCENT VOLATILE: Not determined

FLASH POINT AND METHOD: > (200°F) TCC

VAPOR PRESSURE: Not yet Determined

VAPOR DENSITY: Heavier than air

BOILING POINT: greater than 212 deg F

FREEZING POINT: less than 32 deg F (0 deg C)

SOLUBILITY IN WATER: Complete in all proportions.

EVAPORATION RATE: Not determined

SPECIFIC GRAVITY: 1 to 102

VISCOSITY: Not determined

(VOC): < 1.000 percent (v/v)

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

POSSIBILITY OF HAZARDOUS REACTIONS: Reacts with metals (releases hydrogen, a flammable gas). Reacts vigorously with concentrated alkalis to generate acidic steam.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon, nitrogen, and sulfur, organosulfur, organonitrogen, and hydrocarbon residues, acidic fumes

INCOMPATIBLE MATERIALS: Strong alkalis (bases), chlorine bleach, oxidizing and reducing agents, metals such as iron (causes decomposition) and zinc or magnesium (releases hydrogen gas)

11. TOXICOLOGICAL INFORMATION

ACUTE

NOTES: No toxicity data available for product

EYE EFFECTS: Severe irritation, pain, burns, temporary or permanent loss of vision.

SKIN EFFECTS: Moderate to severe irritation, burns, damage to underlying tissues, and scarring.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data

COMMENTS: Because of the low pH of this product, it would be expected to produce significant ecotoxicity upon exposure to aquatic systems and organisms.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Unused or undiluted product constitutes a hazardous waste. Follow all appropriate local, state, and Federal disposal regulations. Surfactants and other organic components are biodegradable. Collect and neutralize spent solutions and discharge to a waste water treatment facility.

FOR LARGE SPILLS: See Section 6

EMPTY CONTAINER: Triple rinse container thoroughly with water and recycle.

RCRA/EPA WASTE INFORMATION: Unused or undiluted product would constitute an RCRA regulated hazardous waste due to corrosivity (CORROSIVE WASTE - D002, pH equal to or less than 2.0)

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated By U.S. DOT

VESSEL (IMO/IMDG)

SHIPPING NAME: UN1760, CORROSIVE LIQUID, N.O.S. (Urea Hydrochloride), 8, PG III

EmS: F-A, S-B

MARINE POLLUTANT #1: No

PLACARDS: Corrosive

LABEL: Corrosive

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

Not Regulated by U.S. DOT

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute health hazard (eye and skin irritation/corrosion), Reactivity

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** Yes **ACUTE:** Yes **CHRONIC:** No

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Buffered Acid Salt Solution	Proprietary
Ethoxylated Linear Alcohols	Proprietary
Glycol ether	Proprietary

CALIFORNIA PROPOSITION 65: Contains no substances known to the State of California to cause cancer, birth defects, or reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE: Convert to GHS format


APPROVED BY: H. Zeller

PREPARED BY: CSCC **Date Prepared:** 5/26/2015

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	0
PHYSICAL HAZARD	<input type="checkbox"/>	1
PERSONAL PROTECTION	<input type="checkbox"/>	

NFPA CODES



GENERAL STATEMENTS: Amounts specified herein (other than for regulatory purposes) are typical and do not represent a specification. Unspecified or unlisted components are proprietary, do not present a hazard at levels present, are not hazardous, and/or are present at levels below reportable limits. Exact percentage values for all components are proprietary in accordance with 29 CFR 1910.1200(i)

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for its accuracy and/or completeness. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health or physical hazards and should be used with caution. Certain hazards are described herein, but

no guarantee is made that these are the only hazards associated with the material that exist.