

SAFETY DATA SHEET



Date Prepared : 06/10/2015
 SDS No : 5106
 Date Revised : 06/10/2015
 Revision No : 1

SAMSON

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SAMSON
GENERAL USE: Heavy Duty Water Based Cleaner/Degreaser
PRODUCT CODE: 5106

MANUFACTURER

JOHN-HENRY Enterprises, Inc.
 2813 Richland Ave
 Metairie, LA 70002
Emergency Contact: H. Zeller
Emergency Phone: 504-888-8989

24 HR. EMERGENCY TELEPHONE NUMBERS

US/Canada: 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Damage/Irritation (Reversible), Category 2
 Skin Corrosion/Irritation (reversible), Category 2

GHS LABEL

Causes moderate to severe irritation to eyes. Prolonged exposure can cause moderate to severe irritation to skin. Vapors, mists and spray can irritate eyes, nose, throat, and respiratory system. Vapors may cause anesthetic effects



Irritant

SIGNAL WORD: WARNING**HAZARD STATEMENTS**

H319: Causes serious eye irritation.
 H315: Causes skin irritation.
 H335: May cause respiratory irritation.
 H302: Harmful if swallowed.

PRECAUTIONARY STATEMENTS**Prevention:**

P102: Keep out of reach of children.
 P103: Read label before use.
 P262: Do not get in eyes, on skin, or on clothing.
 P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 75990X3S: Keep only in original container. Store in a well-ventilated place. Keep container tightly closed.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Causes moderate to severe irritation to eyes. Prolonged exposure may irritate skin. Mists or sprays may irritate eyes, nose, and throat. Vapors can cause nausea, dizziness, nausea, stupor, vomiting, headache, and/or irritation to nose, throat, and respiratory system.

POTENTIAL HEALTH EFFECTS

EYES: Severely irritating and may cause temporary blurring of vision and temporary damage

SKIN: Prolonged or repeated exposure may cause dryness, redness, rash, irritation, sensitization and/or dermatitis.

INGESTION: Causes irritation to mouth, throat, esophagus, and gastrointestinal system .May cause gastrointestinal discomfort, including nausea, vomiting, diarrhea, etc

INHALATION: Mists or sprays can be moderately to severely irritating to eyes and respiratory tract. Concentrated vapors can cause nausea, dizziness, vomiting, and other symptoms of intoxication.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Synthetic Sodium Silicate	< 3	Proprietary
Glycol ether	5 - 7	Proprietary
Alkaline Builder	< 3	Proprietary
Other ingredients are not hazardous or are present at levels that do not present a significant hazard.	> 85	000-00-1

4. FIRST AID MEASURES

EYES: Gently hold eyelids open and flush with water for 15 minutes or until discomfort eases. Remove contact lenses if possible. Seek medical attention if irritation persists or vision remains blurred.

SKIN: Remove contaminated clothing and footwear. Flush off with water. Get medical attention if irritation develops or persists.

INGESTION: Get immediate medical attention (call 911). Do not induce vomiting unless instructed to do so by poison center or physician. Give patient water or milk unless unconscious or convulsing. Keep patient warm and comfortable. Treat for shock.

INHALATION: If affected by vapors, spray or mist, move to fresh air. Seek medical attention if symptoms persist or worsen.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Moderate to severe irritation, including copious tearing, stinging, burning, temporary blurring of vision

SKIN: Prolonged or repeated contact may produce irritation, redness, edema, burning or itching, rash, etc. Glycol ether can be absorbed by skin and product dizziness, nausea, vomiting, and other signs of CNS depression

INGESTION: Causes moderate to severe irritation to mouth, throat, esophagus, and GI tract. Can cause gastrointestinal discomfort, including nausea, vomiting, and diarrhea.

INHALATION: Vapors, spray or mists can irritate eyes, nose, throat, and respiratory tract. Vapors can cause dizziness, drowsiness, nausea, headache, drunkenness, vomiting, unconsciousness, and other anesthetic effects.

NOTES TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Applicable - Water based product with no flashpoint.

EXTINGUISHING MEDIA: Not applicable - water based product. After water has evaporated, use water (fog or spray) or chemical foam on burning solids.

HAZARDOUS COMBUSTION PRODUCTS: After water has evaporated, burning solids will produce oxides of carbon and sulfur, organosulfur and hydrocarbon residues, acid or acidic fumes

EXPLOSION HAZARDS: Containers can burst if exposed to flames or high temperatures.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting chemical fires. Use water fog or spray to cool containers.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain and absorb spilled material. Dispose of contaminated absorbant properly. Wash spill area with water.

LARGE SPILL: Wear appropriate PPE. Remove uninvolved personnel from area. Stop flow. Contain spill and keep from entering sewer or surface waterways. Collect spill into suitable, properly labeled containers for use or disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

HANDLING: Read and understand product label and SDS before handling any chemical. Always wear recommended personal protective equipment. Follow label cautions and instructions.

STORAGE: Store in original containers in well ventilated area. Keep containers closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
			EXPOSURE LIMITS				
			OSHA PEL		ACGIH TLV		
Chemical Name			ppm	mg/m ³	ppm	mg/m ³	
Glycol ether			TWA	50	240	20	97

ENGINEERING CONTROLS: Maintain sufficient ventilation in storage and use areas to prevent the accumulation of product vapors, spray, or mists. Provide local exhaust for enclosed areas.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Avoid eye contact. Wear safety glasses or goggles

SKIN: Avoid prolonged or repeated contact. Wear rubber, latex, or other chemical resistant gloves.

RESPIRATORY: Use with adequate ventilation. Wear a NIOSH approved air purifying respirator where vapors, mists or spray are excessive or exceed exposure limits.

WORK HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or using the facilities after handling any chemical product.

OTHER USE PRECAUTIONS: Working eyewash stations and safety showers should be located in or near all areas where chemicals are stored or used.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: mild, ether-like

APPEARANCE: clear, purple liquid

pH: 11.0 to 12.0

Notes: (5%)

PERCENT VOLATILE: 85 - 90% (w/w)

FLASH POINT AND METHOD: > (200°F)

VAPOR PRESSURE: Same as water (approximately)

VAPOR DENSITY: Same as water (approximately)

BOILING POINT: greater than 212 deg F

FREEZING POINT: less than 32 deg F (0 deg C)

SOLUBILITY IN WATER: Complete in all proportions.

EVAPORATION RATE: Same as water (approximately)

SPECIFIC GRAVITY: 1.035 to 1.045

(VOC): ~ 7.000

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: No

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and sulfur, organosulfur and hydrocarbon residues

INCOMPATIBLE MATERIALS: oxidizing agents.

11. TOXICOLOGICAL INFORMATION**ACUTE**

NOTES: No toxicity data available for product

EYE EFFECTS: Moderate to severe irritation, including tearing, redness, burning or stinging, temporary blurring of vision.

SKIN EFFECTS: Prolonged or repeated exposure can cause moderate to severe irritation. dermatitis, rash, sensitization. Prolonged one time exposure may cause burns.

CARCINOGENICITY

Chemical Name	General Toxicity
Glycol ether	Confirmed animal carcinogen with unknown relevance to humans - Group A3

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Unused or undiluted product constitutes a hazardous waste. Follow all appropriate local, state, and Federal disposal regulations. Surfactants and other organic components are biodegradable. Collect and neutralize spent solutions and discharge to a waste water treatment facility.

FOR LARGE SPILLS: See Section 6

EMPTY CONTAINER: Triple rinse container thoroughly with water and recycle.

RCRA/EPA WASTE INFORMATION: Unused or undiluted product would constitute an RCRA regulated hazardous waste due to corrosivity (CORROSIVE WASTE - D002, pH equal to or greater than 12.5)

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: NOT REGULATED

VESSEL (IMO/IMDG)

SHIPPING NAME: NOT REGULATED

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute health hazard (eye and skin irritation)

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Alkaline Builder	< 3	5,000

CERCLA RQ: greater than 10000 lbs (as supplied)

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Synthetic Sodium Silicate	Proprietary
Glycol ether	Proprietary
Alkaline Builder	Proprietary

TSCA STATUS: All ingredients are included on the TSCA Inventory or are exempt

CALIFORNIA PROPOSITION 65: Contains no substances known to the State of California to cause cancer, birth defects, or reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE: Convert to GHS format

APPROVED BY: H. Zeller


PREPARED BY: CSCC **Date Revised:** 06/10/2015

REVISION SUMMARY: This SDS replaces the 06/10/2015 SDS. Revised: **Section 1:** 24 HR. EMERGENCY TELEPHONE NUMBERS, GENERAL USE, REASON FOR ISSUE. **Section 2:** EMERGENCY OVERVIEW - IMMEDIATE CONCERNS POTENTIAL HEALTH EFFECTS (SKIN, INHALATION, INGESTION).

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	

NFPA CODES



GENERAL STATEMENTS: Amounts specified herein (other than for regulatory purposes) are typical and do not represent a specification.

Unspecified or unlisted components are proprietary, do not present a hazard at levels present, are not hazardous, and/or are present at levels below reportable limits. Exact percentage values for all components are proprietary in accordance with 29 CFR 1910.1200(i)

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for its accuracy and/or completeness. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health or physical hazards and should be used with caution. Certain hazards are described herein, but no guarantee is made that these are the only hazards associated with the material that exist.